

JOFRA™ mAcal

milliAmp calibrator

Compact loop calibrator ideal for field use



Sources and measures current

Allows for calibration of transmitters in a two-wire loop

Stable source

Internal 24 VDC supply for consistent loop power

High resolution

Read to 0.001 mA in the measurement mode

% of full scale reading

Displays a percentage to provide for easy analysis of results

Fixed step function

Allows you to easily calibrate linear or flow transmitters and valve positioners

Manual or automatic stepping function

You can choose to use either method and have 10 to 30 seconds between steps

Timesaving features

Fast one-key-one-function access to the features such as the step function or loop supply power

Large display


Includes large numbers for unit reading, a percentage display, and dedicated icons for calibrator status including a low battery indicator

Traceable calibration

For your confidence, the unit is supplied with a calibration certificate that is fully traceable to a national standards lab such as NIST or NPL

The mAcal Milliamp Calibrator is an economical and easy-to-use calibration device for sourcing and measuring mA signals.

The instrument is designed specifically for 2-wire transmitter loops with 4 to 20 mA signals and it is delivered with traceable certification.



PRODUCT DESCRIPTION

The JOFRA mAcal keypad is easy-to-use and provides positive tactile feedback to the user. Each key is labeled for easy operation. A large, high-contrast, 5-digit LCD display indicates numeric values in mA, %, V or sec. The resolution is 0.001 mA in measurement mode. The user can change the display to read in % of Full Scale and flow readings are shown in % of Flow.

The display also indicates error codes. Visual warnings are displayed for loop mismatch, reverse polarity and over range. Plus, the unit is equipped with a user adjustable automatic shut-off feature that prevents accidental battery discharge when the unit is not in use. A built-in, permanent fuse eliminates the need to replace the fuse in the case of overloads: no need to return the unit to the factory to reset or replace the fuse.

The mAcal Loop Calibrator provides loop power in the range of 0 to 45 VDC and the instrument is designed to generate a stable 24 VDC supply for the loop.

The mAcal Loop Calibrator also reduces the time and complexity often associated with loop calibration. The instrument features special fixed steps for performing linear and flow transmitter or valve positioner calibrations. The instrument has seven different built-in current values and the user may choose between manual or automatic steps with 10 or 30 seconds between steps. You can perform an entire test by placing the mAcal in the process loop and take readings from the control room.

JOFRA mAcal CALIBRATOR

Mains adapter

Connection to mains adapter.
6 VDC, 230 mA.
Note : The mains adapter does not charge rechargeable batteries.

Connection

Connection of + test lead

Connection

Connection of - test lead

Display

Shows numerical value in mA, %, V or sec., and for readout of error codes etc.

PWR

Switch between external and internal loop power supply EXT. (the +24 VDC of the current loop is generated by an external power supply) and INT. (the +24 VDC of the current loop is generated by the mAcal itself).

FUNC

This key allows for changing functions between SOURCE mA, MEASURE mA and MEASURE Volt function.

ON/OFF

Switching instrument on/off.

Step

The STEP function is activated or de-activated.

mA/% / setup

Alternating between readout in mA and %. If the key is held down for more than 2 sec., a change to SETUP takes place. Under SETUP this key is used to select next parameter.

Up arrow

Functions to increase entered values or to scroll up.

Auto

AUTO ramp or AUTO-STEP function is started or stopped.

Down arrow

Functions to decrease entered values or to scroll down.



JOFRA mAcal in softcase

The mAcal calibrator is available separately and are supplied in a handy softcase that allows for complete operation of the unit while in the case. The convenient internal arrangement offers you the space to store test leads.

FUNCTIONAL SPECIFICATIONS

Current source

Range:.....0 to 24 mA
 Resolution:0.01 mA
 Accuracy (k=2): ±0.05% of F.S.
 Maximum load:900 ohm
 Temperature coefficient:0.005% per °C (-10 to 40°C)
0.003% per °F (-14 to 104°F)

Current measurement

Range:.....0 to 24 mA
 Resolution:0.001 mA
 Accuracy (k=2): ± 0.05% of F.S.
 Input impedance: 10 ohm
 Temperature coefficient:0.003% per °C (-10 to 40°C)
0.002% per °F (-14 to 104°F)

Voltage measurement

Range:..... -45V to +45 VDC
 Resolution:0.1 VDC
 Accuracy: ± 0.5 VDC
 Input impedance: 10M ohm

PHYSICAL SPECIFICATIONS

Instrument weight (incl. batteries, leads and case)

Weight 0.8 lbs /355g

Instrument dimensions (incl. batteries, leads and case)

Size: L x W x H..... 6.85 x 2.6 x 1.0 in / 174 x 66 x 26 mm

Miscellaneous

Operating (ambient) temperature .. -14 to 104°F (-10 to 40°C)
 Storage (ambient) temperature..... -4 to 122°F (-20 to 50°C)
 CE Conformity..... 89/336/EEC, EN50081-1, EN50081-2,
 EN50082-1, EN50082-2, (91/157/EEC)

OTHER SPECIFICATIONS

Power supply

120 VDC Mains Adapters: 103964, 6 VDC / 240 mA US/
 Japan- 1.3mm DC female connector
 Batteries 4 Type LR6, AA, 1.5 VDC Alkaline
 Battery life 200 hours with external loop power
 20 hours with 12 mA output/internal loop power
 Warranty:2-year Factory Warranty



Fig. 1

Adjusting the instrument

Connect the mAcal to an external reference instrument as shown in Fig. 1. The mAcal now carries out a self-calibration and adapts its circuits to that measured. It is now adjusted and ready for use.

Note: The mAcal can only be adjusted in mA. Adjustment of the VDC function is not possible.




Fig. 2

Calibrating the instrument (measure mA)

Connect the mAcal to an external reference instrument and a current source as shown in Fig. 2.

Calibration is carried out in the following points: 0 mA, 4 mA, 8 mA, 12 mA, 16 mA, 20 mA and 24 mA. If the mAcal displays EEEEE when measuring the 24 mA, you must turn down the current until the EEEEE disappears.

Calibration must subsequently be carried out at a lower value (e.g. 23.995 mA).

The deviation between the read value of the mAcal and the read value of the reference instrument must be 8 µA at a maximum.



Fig. 3

Calibrating the instrument (source mA)

Connect the mAcal to an external reference instrument as shown in Fig. 3. Calibration is carried out in the following points: 0 mA, 4 mA, 8 mA, 12 mA, 16 mA, 20 mA and 24 mA. The deviation between the adjusted value of the mAcal and the read value of the reference instrument must be 8 µA at a maximum.

ORDERING INFORMATION

Part No.	Description
75-MACAL	mAcal Calibrator with standard accessories

STANDARD DELIVERY

mAcal Calibrator:

- mAcal
- Soft carrying case
- 2 test leads with crocodile clip
- 4 batteries, type LR6, AA
- User manual

ACCESSORIES

Part no.	Description
103964	120 VAC Adapter (US / Japan)
103950	230 VAC Adapter (Euro)
103957	230 VAC Adapter (UK)
124716	4 x 1,5 Volt rechargeable batteries
124718	Charger for 124716 batteries - 115/230 VAC



temperature
software
pressure
signal



AMETEK

Calibration Instruments

offers a complete range of calibration equipment for pressure, temperature, and signal - including software.

JOFRA Temperature standards

Portable precision thermometer. Dry-block calibrators: 4 series, more than 20 models - featuring speed, portability, accuracy, and advanced documenting functions.

M&G Primary pressure standards

Pneumatic floating-ball or hydraulic piston deadweight testers - easy-to-use with accuracies up to 0.015% of reading.

JOFRA Pressure standards

Convenient electronic systems ranging from -1 to 700 bar (25 inHg to 10,000 psi) - multiple choices of pressure ranges, pumps, and accuracies, fully temperature-compensated for problem-free and accurate field use.

JOFRA Signal calibration

Process signal measurement and simulation for easy control loop calibration and measurement tasks - from handheld field instruments for multi or single signals to laboratory reference level bench top instruments.

...because calibration is a matter of confidence

AMETEK[®]
CALIBRATION INSTRUMENTS

www.ametekcalibration.com
www.jofra.com

AMETEK is a leading global manufacturer of electrical and electromechanical products for niche markets. AMETEK's annual sales exceed \$1 billion. NYSE (AME) since 1930. Operations are in US, Europe and Asia, with about 1/3 of sales to markets outside the US.

AMETEK Test & Calibration Instruments
USA, Florida Tel: +1 (727) 536-7831
Tel: (800) 527-9999
calinfo.us@ametek.com

AMETEK Denmark A/S
Denmark Tel: +45 4816 8000
ametek@ametek.dk

Distributor:

AMETEK Singapore Pte. Ltd.
Singapore Tel: +65 6 484 2388
aspl@ametek.com.sg

AMETEK GmbH
Germany Tel: +49 2159 9136 0
info@ametek.de

Pub Code **SS-CP-2320-US Issue 0408**

ISO 9001 Manufacturer

Information within this document is subject to change without notice.

Copyright 2004 by AMETEK, Inc.
AMETEK is a registered trademark of AMETEK, Inc.